



» VARIUS MACHINES GUARDS

PBF 10

PRODUCT SHEET

Last update:
07/02/2024



FEATURES

Protects the operator from direct contact with dangerous parts frontally segregated by the shield.
Frontally attachable to the machine. Equipped with wide "visibility" reversible opening shield: vertical or horizontal and left or right, with position-release knob. Equipped with safety microswitch.

-Note:specify the mounting side by adding the suffix: /**DX** = Right - /**SX** = Left
-Available accessories: **PBA 01/190 - PBA 01/325 - PBA 02/325**

1. Angular anchorage stirrup – in pressed steel
2. Articulated arms – in tubular steel
3. Rubbing articulation with friction disc
4. Angular junction for vertical turnover of the shield
5. Main box with 180° rotation and safety microswitch with n. 2 NC contacts
6. Shield-opening release knob
7. Shield structure – in aluminium profile
8. Shield – in plastic shockproof and oil-resistant material

Universal rubbing articulated arms guard, with reversible opening direction. Practical and immediately adjustable. Designed for frequent changes of operation.

CODE	A	B	KG
PBF 10/350/...	350	300	5,5
PBF 10/435/...	400	350	5,8

Our protections comply with the machinery directive 2006/42/CE

CE
<https://www.tecnopiu.it/>