



»» MILLS GUARDS

# PFR 01

## PRODUCT SHEET

Last update:  
04/13/2023



### FEATURES

Protects the operator from direct contact with rotating parts of the vertical spindle and from the projection of shavings and lubricant-coolant.

Attachable on the base flank, equipped with semi-circular shield with double opening system:

- 1) shield openable horizontally on its axis
- 2) "swinging" total of the safety guard, outside the field of work. Complete with double safety microswitch.

-Note: Specify the mounting side by adding the suffix: /DX = Right - /SX = Left

-Available accessories: PMG 60/185 - PBA 01/190 - PBA 01/325 - PBA 02/325

1. Levelling anchorage stirrup - in tubular steel
2. Depth-adjustable safety guard support
3. Safety microswitch main box - 180° rotation - n. 2 NC contacts
4. Horizontal adjustment clamp
5. Articulated arms - in tubular steel
6. Rubbing articulation with friction disc
7. Shield-arm connection clamp in pressed steel
8. Shield structure - in tubular steel
9. Thermo-formed shield - in plastic shockproof and oil-resistant material

Classic universal safety guard with articulated arms. The rubbing articulations make it particularly versatile and able for immediate placement. Available in various dimensions.

CODE	A	B	KG
PFR 01/300/...	300	200	9,5
PFR 01/400/...	400	235	9,8
PFR 01/500/...	500	235	10,1
PFR 01/600/...	600	235	10,4

Our protections comply with the machinery directive 2006/43/CE

**CE**  
<https://www.tecnopiu.it/>