



» LATHE GUARDS

PLT 02

PRODUCT SHEET

Last update:
04/13/2023



FEATURES

Allows the activation of chuck rotation, performing a forced “double movement” manoeuvre. Suitable for installation on machines with one or two levers. Provided in a single piece, to replace only one of the two original machine levers, normally identified as the most frequently used one, while the original remaining lever remains operational only for disconnection.

Equipped with universal leveling plate where a hole must be made that corresponds to the central “neutral” position – In this way, the safety bolt on the joint enters into the hole which in turn, in case of involuntary activation, sets the lever locking.

Activation of the chuck rotation occurs by performing in sequence: movement 1° and subsequently movement 2° disconnection occurs by directly performing movement 2° until the introduction of the safety bolt into the locking hole.

1. Adjustable angular anchorage stirrup – in pressed steel
2. Leveling plate, to insert the locking pivot – in pressed steel
3. Shalt to be inserted in the original joint of the chuck bar – in steel
4. Joint equipped with safety pivot and recall spring – in steel
5. Adjustable safety bolt
6. Manoeuvre lever equipped with round knob

Double-movement universal device, for the insertion of chuck rotation. Provided in a single piece, to be installed as a replacement for one of the two original levers.

Our protections comply with the machinery directive 2006/43/CE

CE
<https://www.tecnopiu.it/>