



»» **LATHE GUARDS**

# PTO 04

PRODUCT SHEET

Last update:  
04/13/2023



**FEATURES**

Prevents the operator from direct contact with rotating chuck lathe and helps in containing the lubricant-coolant and the working swarfs.  
The strong support structure (point 1), fully "X - Y" adjustable, allows easy anchoring on the rear side of the machine and, if necessary, also on the front. Equipped with semicircular shield, divided into two sections to allow opening of only the front side (point 6) or total opening, overturning it completely towards the back.  
Complete with double safety microswitch.

1. Anchorage and support structure of the shield, adjustable in the X - Y axes
- 2-3. Safety microswitches of the two shield opening systems - n. 2 NC contacts
4. Adjustable structure to support the shield on the lathe head
5. Shield made of aluminium sheet and profiles, completely overturnable on the back or lockable through a special system of its rotation axis.
6. Front section of the shield designed for frequent openings during working operations

Remarkably strong item, designed for chuck lathes up to Ø 1000 mm. Equipped with shield which can be opened totally or partially. Available in various dimensions

CODE	A	B	C	D	E	KG.
PTO 04/080	800	300	400	165-375	5-120	17,1
PTO 04/100	1000	350	500	265-475	5-70	19,7
PTO 04/120	1200	350	600	365-575	5-70	21,7

Our protections comply with the machinery directive 2006/43/CE

**CE**  
<https://www.tecnopiu.it/>