



»» **LATHE GUARDS**

PTO 20

PRODUCT SHEET

Last update:
04/13/2023



FEATURES

Protects the operator from direct contact with rotating components of the chuck and from the projection of shavings and lubricant-coolant. Attachable on the machine head, equipped with wide "visibility" sliding shield, with various adjustments for an easy adaptation to all machines. Available in three sizes, up to a Ø chuck of 800-900 mm. Complete with safety microswitch.

1. Anchorage stirrup with wide vertical adjustment
2. Sliding mobile protection support carriage
3. Auto-carrying guide - in extruded aluminium, with sliding system composed from tempered and rectified steel guides-bearings, placed in protected internal position
4. Safety microswitch with separated actuator - n. 2 NC contacts
5. Shield structure - in tubular steel and aluminium
6. Shield - in shockproof and oil-resistant plastic material, of great thickness

Particularly solid and functional item, designed for the secure protection of the operator from moving parts of the lathe. To be fixed on the machine head.

CODE	Ø	A	B	C	D	E	F	G	KG
PTO 20/400	400-500	450	430	655	480	350	125	280-540	26,6
PTO 20/600	600-700	450	520	855	640	430	150	320-740	27,7
PTO 20/800	800-900	450	640	1065	800	530	180	370-950	28,8

Our protections comply with the machinery directive 2006/43/CE

CE
<https://www.tecnopiu.it/>