



»» **LATHE GUARDS**

# PTO 21

PRODUCT SHEET

Last update:  
04/13/2023



**FEATURES**

Protects the operator from direct frontal contact with rotating components of the chuck and from projection of shavings and lubricant-coolant. The main feature is the sliding shield included in a solid and light aluminium structure, equipped with four anchorage points on the machine head, allowing to keep the shield in a overhanging position.

The sliding shield has a wide visual manufactured with a special material, suitable to be used for safety guards.

Available in different sizes, up to a Ø chuck of 800-1200 mm. Complete with safety microswitch.

The structure can be also customized for much bigger chucks.

1. Supporting structure with steel guides
  2. Sliding carriage with bearings
  3. Double steel guide for carriage sliding
  4. Interlocked microswitch
  5. Removable aluminium frame
  6. Steel-sheet protection panel
1. Polycarbonate transparent protection shield

Sliding shield for big dimension lathe, designed to be fixed on the machine head, making the whole structure of the guard stable.

CODE	A	B	C	D	E	F	G	H	I	KG
PTO 21/080	550	1000	1000	518	282	800	300	390-590	930-1490	-
PTO 21/120	550	1500	1400	918	282	1200	300	390-590	930-1490	-
PTO 21/S	-	-	-	-	282	-	300	-	-	-

Our protections comply with the machinery directive 2006/43/CE

