



» **ELECTRICAL PANEL**

QGE 16

PRODUCT SHEET

Last update:
04/12/2023



Kit for generic machines, with pressed steel case equipped with door (whose opening is only allowed when the general switch is "Off") and protection against short circuits and current overloads. Complete with general magnetothermic safety switch arranged for padlock, n. 2 contactors, 400/24 VAC transformer, n. 2 auxiliary circuit protection fuses, emergency mushroom-shaped pushbutton and double start-stop button, with voltage warning light, auxiliary output protected by thermal relay. Panel for machines with absorption Max = 7.5KW

- On request: QGE 16.01 for machines with Max absorption = 11KW

- On request: QGE 16.02 for machines with Max absorption = 15KW

BOX DIMENSION (W x H x D): 250x300x150mm

OPTIONAL: Bracket RZA 62

Minimum voltage coil on general switch

Our protections comply with the machinery directive 2006/43/CE


<https://www.tecnopiu.it/>

IMPORTANT: When placing an order, notify the maximum absorption of the machine and of the auxiliary power, in Ampere (or KW) and the voltage.

Our protections comply with the machinery directive 2006/43/CE


<https://www.tecnopiu.it/>



via Pio la Torre, 5 - 61010 Tavullia (PU) - Italy - VAT ID: 03657250407
Phone n°: +39 0721 476381 - Fax: +39 0721 476608 - Mail: info@tecnopiu.it