



» **ELECTRICAL PANELS WITH MOTOR BRAKE**

QGE 25

PRODUCT SHEET

Last update:
04/13/2023



Kit for generic machines, with metal case equipped with door (whose opening is only allowed when the general switch is "Off") and protection against short circuits and current overloads. Complete with general magnetothermic safety switch arranged for padlock, n. 3 contactors, 400/24 VAC transformer, **electronic motor brake device with DC injection (Exclusive Tecno Più)**, n. 4 fuses, emergency mushroom-shaped pushbutton and start-stop button with motor start warning light, voltage warning light and 2-channel safety module with reset button and warning-light for brake failure.

Panel for machines with Max absorption = 7,5KW at a voltage of 400V.

BOX DIMENSION (W x H x D): 300x300x150mm

OPTIONAL: BRACKET RZA 62

Minimum voltage coil on general switch

Our protections comply with the machinery directive 2006/43/CE


<https://www.tecnopiu.it/>

IMPORTANT: When placing an order, notify the maximum absorption of the machine, in Ampere (or KW) at a voltage of 400V.

Our protections comply with the machinery directive 2006/43/CE


<https://www.tecnopiu.it/>



via Pio la Torre, 5 - 61010 Tavullia (PU) - Italy - VAT ID: 03657250407
Phone n°: +39 0721 476381 - Fax: +39 0721 476608 - Mail: info@tecnopiu.it