

## >> ELECTRICAL PANELS WITH MOTOR BRAKE

## **QGE 30**

PRODUCT SHEET

Last update: 04/13/2023



Kit for generic machines with metal case equipped with door (whose opening is only allowed when the general switch is "Off") and protection against short circuits and current overloads. Complete with general magnetothermic with minimum voltage coil, arranged for padlock, n. 2 contactors, 400/24 VAC transformer, **electronic motor brake device with DC injection (Exclusive Tecno Più),** n. 4 fuses, emergency mushroom-shaped pushbutton and double start-stop button with motor start warning light, voltage warning light, AXS 125 KHz access control and auxiliary output protected by thermal relay.

Panel for machines with Max absorption = 7,5KW at a voltage of 400V.

- On request: QGE 31 with AXS 13,5 MHz access control.

BOX DIMENSION (W x H x D): 400x300x150mm

OPTIONAL: BRACKET RZA 62

IMPORTANT: When placing an order, notify the maximum absorption of the machine and of the

Our protections comply with the machinery directive 2006/43/CE





auxiliary power, in Ampere (or KW) and the voltage.	
Our protections comply with the machinery directive 2006/43/CE	https://www.tecnopiu.it/
TECNOPIU >>>	nttps://www.tecnopiu.it/